



Hints and features:

- The Ceat Torquemax is a tyre for high power tractors
- The casing construction provides low soil compaction, high traction, riding comfort on an off the road
- The tread lugs are higher angled an slightly overlapping in the tread center for good rolling properties on the road
- Lower lug angles on the tyre shoulder grant excellent traction in the field
- Rounded tyre shoulders protect soil and crop from damages

Abroncs IF 710 / 70 R 42, Torquemax 179 D, TL CEAT

Product-No.: 15126980

Technical Information:

Product number	15126980
Tyre Size	IF 710 / 70 R 42
R/D	Radiális
TL / TT	TL
LI/SI	179 D
Tread	Torquemax
Manufacturer	CEAT
Recom. Rim	DW25B
Permissible rim	DW23B
Width mm	720
Outer diameter mm	2061
Static radius mm	930
Rolling circumference mm	6120
Payload in kg at kph (1)	7750 / 65
Inflation pressure bar	2,40
Weight kg	335
Stud height mm	60,0
Certified	ECE 106
Nominal width [mm]	710
Aspect ratio	70
Tyre technology	IF
Direction bound	Yes
Tread symmetry	szimmetrikus

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Kft. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.