



## Hints and features:

- The Ceat Torquemax is a tyre for high power tractors
- The casing construction provides low soil compaction, high traction, riding comfort on an off the road
- The tread lugs are higher angled an slightly overlapping in the tread center for good rolling properties on the road
- Lower lug angles on the tyre shoulder grant excellent traction in the field
- Rounded tyre shoulders protect soil and crop from damages

Abroncs VF 600 / 70 R 30, Torquemax 170 D, TL, Textil Belted CEAT

Product-No.: 15126846

## **Technical Information:**

Product number	15126846
Tyre Size	VF 600 / 70 R 30
R/D	Radiális
TL/TT	TL
LI/SI	170 D
Tread	Torquemax
Manufacturer	CEAT
Specification	Textil Belted
Recom. Rim	DW21L
Permissible rim	DW20L
Width mm	603
Outer diameter mm	1602
Static radius mm	726
Rolling circumference mm	4731
Payload in kg at kph (1)	6000 / 65
Inflation pressure bar	2,40
Weight kg	188,6
Stud height mm	53,5
Certified	ECE 106
Nominal width [mm]	600
Aspect ratio	70
Tyre technology	VF
Direction bound	Yes
Tread symmetry	szimmetrikus

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Kft. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.