



Hints and features:

- The Ceat Torquemax is a tyre for high power tractors
- The casing construction provides low soil compaction, high traction, riding comfort on an off the road
- The tread lugs are higher angled an slightly overlapping in the tread center for good rolling properties on the road
- Lower lug angles on the tyre shoulder grant excellent traction in the field
- Rounded tyre shoulders protect soil and crop from damages

Abroncs VF 710 / 60 R 38 NRO, Torquemax 171 D, TL, Steel Belted CEAT

Product-No.: 10000658

Technical Information:

Product number	10000658
Tyre Size	VF 710 / 60 R 38 NRO
R/D	Radiális
TL / TT	TL
LI/SI	171 D
Tread	Torquemax
Manufacturer	CEAT
Specification	R1-W, Steel Belted
Recom. Rim	DW25B
Permissible rim	DW24B, DW27B
Width mm	710
Outer diameter mm	1820
Static radius mm	799
Rolling circumference mm	5375
Payload in kg at kph (1)	6150 / 65
Inflation pressure bar	1,60
Weight kg	249,50
Stud height mm	51,5
Number of studs	20x2
Certified	ECE 106
NRO	NRO
Nominal width [mm]	710
Aspect ratio	60
Tyre technology	VF
Direction bound	Yes
Tread symmetry	szimmetrikus

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Kft. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.