Bohnenkamp Moving Professionals



Hints and features:

- The Ceat Torquemax is a tyre for high power tractors
- The casing construction provides low soil compaction, high traction, riding comfort on an off the road
- The tread lugs are higher angled an slightly overlapping in the tread center for good rolling properties on the road
- Lower lug angles on the tyre shoulder grant excellent traction in the field
- Rounded tyre shoulders protect soil and crop from damages

Abroncs VF 540 / 65 R 30, Torquemax 158 D, TL, Steel Belted CEAT

Product-No.: 10000325

Technical Information:

Product number	10000325
Tyre Size	VF 540 / 65 R 30
R / D	Radiális
TL / TT	TL
LI / SI	158 D
Tread	Torquemax
Manufacturer	CEAT
Specification	R1-W, Acél öves
Recom. Rim	DW20B
Permissible rim	DW18L
Width mm	550
Outer diameter mm	1464
Static radius mm	635
Rolling circumference mm	4323
Payload in kg at kph (1)	4250 / 65
Inflation pressure bar	2,00
Weight kg	147,50
Stud height mm	46,5
Number of studs	21x2
Certified	ECE 106
NRO	NRO
Nominal width [mm]	540
Aspect ratio	65
Tyre technology	VF
Direction bound	Yes
Tread symmetry	szimmetrikus

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp Kft. does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.